optomaeurope.com



S334e Bright projection





- Bright SVGA projector 3800 ANSI lumens
- Easy connectivity HDMI, VGA, USB Power
- Clear, powerful audio 10W speaker
- Lightweight and portable

Project bright vibrant presentations effortlessly any time of day. Designed for meeting rooms and classrooms, the S334e boasts amazing colour, long lamp life and energysaving features to provide you with a low overall cost of ownership.



Specifications

Display/image	
Display technology	
Resolution	SVGA (800x600)
Brightness	3,800 lumens
Contrast ratio	22,000:1
Native aspect ratio	4:3
Aspect ratio - compatible	16:9
Keystone correction - vertical	+/-40°
Horizontal scan rate	15.38 ~ 91.15Khz
Vertical scan rate	50 ~ 85(120 for 3D)Hz
Uniformity	75%
Screen size	0.71m ~ 7.73m (27.78" ~ 304.4") diagonal
Lamp info	
Light source type	Lamp
Lamp watts	203
Lamp life hours (up to)	6000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)
Optical	
Throw ratio	1.94:1 ~ 2.16:1
Projection distance (m)	1m - 12m
Zoom	1.1
Zoom type	Manual
Focal length (mm)	21.85 ~ 24
Native offset	115%
Connectivity	
Connections	Inputs 1 × HDMI 1.4a 3D support, 1 × VGA (YPbPr/RGB), 1 × Composite video, 1 × Audio 3.5mm
	Outputs 1 x Audio 3.5mm, 1 x USB-A power 1A
General	
Noise level (typical)	27dB
Noise level (max)	29dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N,
	4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D	3D ready
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (Emplified), Spanish, Swedish, Chinese (Inselfung), Turkish, Vetanogoa
o	(traditional), Turkish, Vietnamese
Operating conditions	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max
	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%
Remote control	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max
Remote control Speaker count	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Card style 1
Remote control Speaker count Watts per speaker	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Card style 1 10W
Remote control Speaker count Watts per speaker	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Card style 1 10W AC power cord
Remote control Speaker count Watts per speaker	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Card style 1 10W AC power cord Remote control
Remote control Speaker count Watts per speaker	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Card style 1 10W AC power cord Remote control Battery
Remote control Speaker count Watts per speaker In the box	5°C-40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Card style 1 10W AC power cord Remote control Battery Basic user manual
Remote control Speaker count Watts per speaker In the box Optional wireless models	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Card style 1 10W AC power cord Remote control Battery
Remote control Speaker count Watts per speaker In the box Optional wireless models Power	5°C-40°C/41°F-104°F, max altitude 3000M/9843ft, max humidity 85% Card style 1 10W AC power cord Remote control Battery Basic user manual HDCast Pro, QuickCast Bundle, WHD200
Remote control Speaker count Watts per speaker In the box Optional wireless models Power Power supply	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Card style 1 10W AC power cord Remote control Battery Basic user manual HDCast Pro, QuickCast Bundle, WHD200 100 ~ 240V, 50 ~ 60Hz
Remote control Speaker count Watts per speaker In the box Optional wireless models Power Power supply Power consumption	5°C-40°C/41°F-104°F, max altitude 3000M/9843ft, max humidity 85% Card style 1 10W AC power cord Remote control Battery Basic user manual HDCast Pro, QuickCast Bundle, WHD200
Remote control Speaker count Watts per speaker In the box Optional wireless models Power supply Power consumption (standby)	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Card style 1 10W AC power cord Remote control Battery Basic user manual HDCast Pro, QuickCast Bundle, WHD200 100 ~ 240V, 50 ~ 60Hz 0.5W
Operating conditions Remote control Speaker count Watts per speaker In the box Optional wireless models Power Power supply Power consumption (standby) Power consumption (min) Power consumption (max)	5°C-40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Card style 1 10W AC power cord Remote control Battery Basic user manual HDCast Pro, QuickCast Bundle, WHD200 100 ~ 240V, 50 ~ 60Hz 0.5W 187W
Remote control Speaker count Watts per speaker In the box Optional wireless models Power Power supply Power consumption (standby) Power consumption (min) Power consumption (max)	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Card style 1 10W AC power cord Remote control Battery Basic user manual HDCast Pro, QuickCast Bundle, WHD200 100 ~ 240V, 50 ~ 60Hz 0.5W
Remote control Speaker count Watts per speaker In the box Optional wireless models Power Power supply Power consumption (standby) Power consumption (min) Power consumption (max) Weight and dimensions Dimensions (W x D x H)	5°C-40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Card style 1 10W AC power cord Remote control Battery Basic user manual HDCast Pro, QuickCast Bundle, WHD200 100 ~ 240V, 50 ~ 60Hz 0.5W 187W
Remote control Speaker count Watts per speaker In the box Optional wireless models Power Power supply Power consumption (standby) Power consumption (min)	5°C-40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Card style 1 10W AC power cord Remote control Battery Basic user manual HDCast Pro, QuickCast Bundle, WHD200 100 ~ 240V, 50 ~ 60Hz 0.5W 187W 225W





Copyright © 2021, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 15042021075611