


DS318e

Bright projection



- **Bright SVGA projector – 3600 ANSI lumens**
- **Easy connectivity – HDMI, VGA, USB Power**
- **Clear, powerful audio - 10W speaker**
- **Lightweight and portable**

Project bright vibrant presentations effortlessly any time of day. Designed for meeting rooms and classrooms, the DS318e boasts amazing colour, long lamp life and energy-saving features to provide you with a low overall cost of ownership.

This projector is easy to connect to with multiple inputs, a built-in speaker and USB Power. Perfect for connecting HDMI dongles such as the Optoma HDCast Pro and the Google Chromecast or a laptop, PC or Blu-ray player for clear projected images with sound. Portable and lightweight projector can be installed or taken on the move for off-site meetings with the optional carry bag (sold separately).



Specifications

EAN: 5055387662124, Colour: Black

Display/imagen

Tecnología de visualización	DLP™
Resolución	SVGA (800x600)
Brillo	3.600 lúmenes
Ratio de contraste	20.000:1
Relación de aspecto nativo	4:3
Ratio de aspecto - compatible	16:9
Corrección Keystone- Vertical	+/-40°
Frecuencia de muestreo horizontal	15,38 ~ 91,15Khz
Frecuencia de muestreo vertical	50 ~ 85(120 for 3D)Hz
Uniformidad	75%
Tamaño de pantalla	0.71m ~ 7.73m (27.78" ~ 304.4") diagonal

Info Lámpara

Fuente de luz	Lámpara
Vatios lámpara	203
Vida de lámpara (horas)	6000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)

Óptica

Distancia de tiro	1.94:1 ~ 2.16:1
Distancia de proyección (m)	1m - 12m
Zoom	1.1
Tipo de zoom	Manual
Distancia focal (mm)	21.85 ~ 24
Offset nativo	115%

Conectividad

Conexiones	Inputs 1 x HDMI 1.4a / 3D , 1 x VGA (YPbPr/RGB), 1 x Video compuesto, 1 x Audio 3.5mm Outputs 1 x VGA, 1 x Audio 3.5mm, 1 x Alimentación USB-A 1A Control 1 x RS232
------------	--

General

Nivel sonoro (típico)	27dB
Nivel sonoro (max)	29dB
Compatibilidad PC	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
Compatibilidad 2D	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D	3D ready
Seguridad	Security bar, Kensington Lock, Password protected interface
Idiomas OSD / display	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
Condiciones de funcionamiento	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Control remoto	Mando tipo tarjeta extraplano
Altavoces	1
Wattios por altavoz	10W
Contenido de la caja	AC power cord Remote control Battery Basic user manual
Modelos inalámbricos opcionales	HDCast Pro, QuickCast starter kit, WHD200

Corriente

Fuente de alimentación	100 ~ 240V, 50 ~ 60Hz
Consumo energético (standby)	0.5W
Consumo energético (mín.)	187W
Consumo energético (máx.)	225W

Peso y dimensiones

Dimensiones (ancho x profundidad x alto)	316 x 244 x 108
Peso bruto	3.52 kg
Peso neto	2.99 kg

