


UHD370X

Lights on viewing 4K Ultra HD projector









- 4K UHD resolution and HDR compatible
- Lights on viewing 3500 ANSI lumens
- Amazing colour accurate Rec.709 colours
- Built-in media player and PureMotion

Immerse yourself in a world of Ultra HD. The UHD370X delivers the ultimate in home entertainment with bright 4K images. You can now enjoy accurate colours, crystal clear detail, and sparkling contrast for a stunningly immersive experience.



Specifications

Watts per speaker

Optional wireless models

Power consumption (min)

Power consumption (max)

Weight and dimensions Dimensions (W x D x H)

In the box

Power

(standby)

mm Gross weight

Net weight

Power supply Power consumption

Display/image	
Display technology	DLP
Resolution	UHD (3840x2160)
Brightness	3.500 lumens
Contrast ratio	500.000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3
Horizontal scan rate	31 ~ 135Khz
Vertical scan rate	24 ~ 120Hz
Uniformity	75%
Screen size	0.87m ~ 7.68m (34.1" ~ 302.4") diagonal
Lamp info	
Light source type	Lamp
Lamp watts	240
Lamp life hours (up to)	4000 (Bright), 15000 (Dynamic), 10000 (Eco)
Optical	
Throw ratio	1.21:1 ~ 1.59:1
Projection distance (m)	1.2m - 8.1m
Zoom	1.3
Zoom type	Manual
Focal length (mm)	12.81 ~ 16.74
Lens shift	Vertical +10%
Native offset	105%
Connectivity	
Connections	Inputs 2 x HDMI 2.0, 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm
	Outputs 1 x Audio 3.5mm, 1 x S/PDIF, 1 x USB-A power 1.5A
	Control 1 x USB-A service, 1 x RS232, 1 x RJ45, 1 x 12V
	trigger, 2 x USB-A reader/wireless
General	
Noise level (typical)	25dB
Noise level (max)	27dB
PC compatibility	UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish
Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Remote control	Backlit home remote
Speaker count	2
	_

5W

0.5W

249W

305W

6.76 kg

5.22 kg

392 x 281 x 118

Lens cap AC power cord Remote control 2x AAA batteries Basic user manual WUSB

100 ~ 240V, 50 ~ 60Hz



