

ML330

Ultra-compact Android LED projector



- **HD Ready and LED technology - Great for movies, gaming and PC-free presentations**
- **Great connectivity - HDMI, MHL, microSD, USB, wireless, Bluetooth and built-in speaker**
- **Stream online content - Built in Android™ v4.4**
- **Compact and lightweight - only 460g**

Conveniently stream content from popular apps without the hassle of connecting a Blu-ray player, media box, dongle, smartphone or tablet. With built-in WiFi and integrated Android™ the ML330 is truly a smart projector, so you can enjoy high definition big screen entertainment in any room in your home.



Specifications

Display/image	
Display technology	DLP
Resolution	WXGA (1280x800)
Brightness (LED)	500 LED brightness
Contrast ratio	20,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3,16:9
Keystone correction - vertical	+/-40°
Has vertical auto keystone correction	Yes
Horizontal scan rate	15 ~ 93Khz
Vertical scan rate	24 ~ 85(120 for 3D)Hz
Uniformity	85%
Screen size	0.25m ~ 3.05m (10" ~ 120") (diagonal)
Lamp info	
Light source type	LED
LED life	20,000 hours
Optical	
Throw ratio	1.2:1
Projection distance (m)	0.26m - 3.09m
Zoom type	Fixed
Focal length (mm)	12
Native offset	100%
Connectivity	
Connections	Inputs 1 x HDMI 1.4a 3D support + MHL, 1 x microSD card, 2 x USB-A reader, 1 x Audio 3.5mm, 1 x DC Outputs 1 x Audio 3.5mm Control 1 x RJ45
General	
Noise level (typical)	34dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Frame-pack: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	8 languages: English, French, German, Italian, Portuguese, Russian, Spanish
Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Remote control	Card style
Speaker count	2
Watts per speaker	1W
In the box	Carry bag HDMI cable AC power cord Remote control Battery Basic user manual
Input lag	16.00ms
Networking	
LAN - control	Yes
Power	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	16W
Power consumption (max)	26W
Weight and dimensions	
Net weight	0.46kg
Dimensions (W x D x H) mm	157 x 122 x 35

