

ZU2200

Ultra bright professional WUXGA laser projector



- **High brightness WUXGA DLP laser projector - 22,000 lumens**
- **Extreme installation flexibility - Eight interchangeable lenses**
- **Ultimate reliability - Built-in redundancy mode**
- **Striking lifelike images - Pure engine video processing and colour matching**

The high brightness ZU2200 professional laser projector fills a need for high-end installations, including the entertainment, exhibition, and digital signage markets. Part of Optoma's Ultra Bright Series, this projector offers incredibly high brightness of 22,000 lumens as well as extreme flexibility with eight interchangeable lenses to meet the needs of even the most complex installations.

As part of the Optoma DuraCore laser line up, the Ultra Bright Series high-performance projectors feature 4K HDR compatibility, pure engine video processing and colour matching to produce visually striking, lifelike images with exceptional detail and high colour accuracy. Additionally, the ZU2200 achieves superior colour rendition through MultiColor Laser (MCL) technology.

Strong reliability is at the core of the Ultra Bright Series projectors, with 24/7 operation capabilities, up to 30,000 hours of laser lifetime, and an IP5X rating for optimal and dependable performance, even under more extreme conditions up to 122 degrees Fahrenheit / 50 degrees Celsius. With a robust metal chassis and modular design for easier maintenance, a multitude of connectivity options, and failsafe redundancy mode for instant source switching, the Ultra Bright Series projectors offer a solution for intricate installations, including multi-projector and dome projection applications.

Specifications

EAN: 5055387665729, Colour: Black

Display/image	
Display technology	DLP
Resolution	WUXGA (1920x1200)
Brightness	22,000 lumens
ANSI brightness	18,500
Contrast ratio	2,000,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	16:9,16:10
Screen size	Dependent on lens
Lamp info	
Light source type	DuraCore MultiColor Laser
LASER life	30,000 hours
Optical	
Throw ratio	Dependent on lens
Projection distance (m)	Dependent on lens
Lens options	BX-CTA11, 0.65~0.75:1
	BX-CTA18, 0.84~1.02:1
	BX-CTA19, 1.02~1.36:1
	BX-CTA20, 1.2~1.5:1
	BX-CTA21, 1.5~2.0:1
	BX-CTA22, 2.0~4.0:1
	BX-CTA23, 4.0~7.2:1
	BX-CTA27, 7.2~10.8:1
Connectivity	
Connections	
Inputs 1 x RS232, 1 x 3D sync, 1 x Wired remote, 1 x HDBaseT, 1 x DisplayPort, 2 x HDMI, 1 x VGA, 1 x DVI-D, 1 x 3G-SDI	
Outputs 1 x RS232, 1 x 3D sync, 1 x Wired remote, 1 x HDMI, 1 x 3G-SDI	
Control 1 x RJ45, 1 x USB-A service, 1 x 12V trigger	
LAN - wireless networking	
No	
General	
Noise level (min)	38dB
Noise level (max)	40dB
3D	Full 3D
IP rating	IP5X
OSD / display languages	
11 languages: Dutch, English, French, German, Hungarian, Italian, Japanese, Norwegian, Polish, Portuguese, Spanish	
24/7 operation	
Yes	
360° operation	
Yes	
Operating conditions	
Operating: 10~85%RH, non-condensing. Storage: 5~90%RH, non-condensing	
Remote control	
Backlit ProAV remote	
Networking	
LAN - display	
Yes	
LAN - wireless networking	
No	
LAN	
Yes	
Power	
Power supply	AC 100~240 V @ 50/60 Hz
Power consumption (standby)	0.5W
Power consumption (min)	590W
Power consumption (max)	1,200W
Weight and dimensions	
Dimensions (W x D x H) mm	650 x 682 x 300.86
Gross weight	66.5 kg
Net weight	54 kg

