

## DW315+

Widescreen, bright and portable









- Bright WXGA projector 3600 ANSI lumens
- Easy connectivity HDMI, VGA, 2W speaker
- Low cost of ownership up to 15,000 hours<sup>2</sup> lamp life
- Lightweight and portable

Project your presentations effortlessly in HD any time of day with the bright DW315+. Designed for meeting rooms and classrooms, this compact projector boasts high brightness, long lamp life and energy-saving features for a low overall cost of ownership.

It is easy to setup with multiple inputs and a built-in speaker - perfect for connecting a laptop, PC or Blu-ray player for clear projected images with sound. Portable and lightweight, this projector can be installed or taken on the move for off-site meetings with the optional carry bag (sold separately).



## **Specifications**

Display/image Display technology DIP

Resolution WXGA (1280x800) Brightness 3,600 lumens Contrast ratio 20,000:1 Native aspect ratio 4:3 Aspect ratio - compatible 16:9.16:10 Keystone correction -+/-40°

vertical

Horizontal scan rate Vertical scan rate

Uniformity 0.68m ~ 8.04m (26.87" ~ 316.5") (diagonal) Screen size

Lamp info Light source type Lamp Lamp watts 195

Lamp life (hours) 5000 (Bright), 7000 (Dynamic), 6000 (Eco), 8000 (Eco+),

15.3 ~ 91.1Khz

24 ~ 85(120 for 3D)Hz

15000 (Education)

15,000 hours Lamp life (education)

Ontical 1.55:1 - 1.73:1 Throw ratio Projection distance (m) 1m - 12m Zoom 1.1 Zoom type Manual Focal length (mm) 21.86 ~ 24

Native offset Connectivity

Connections Inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB),

1 x Composite video, 1 x Audio 3.5mm Outputs 1 x Audio 3.5mm, 1 x USB-A power 1A

Control 1 x BS232

General Noise level (typical)

PC compatibility FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 2D compatibility

4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack

3D compatibility 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60

3D Full 3D

Security Security bar, Kensington Lock, Password protected interface

25 language OSD / display languages

A rabio, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Arabio, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Arabio, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Arabio, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Arabio, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Arabio, Czech, Polish, Portuguese, Romanian, Arabio, Czech, Polish, Po

(simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese

Operating conditions 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m

Remote control Card style Speaker count Watts per speaker 2W

In the box AC power cord, remote control, Battery, basic user manual

Power

Power supply 100 ~ 240V, 50 ~ 60Hz

Power consumption 0.5W (standby)

Power consumption (min) 187W Power consumption (max)

Weight and dimensions

2.17kg Net weight Dimensions (W x D x H) 298 x 230 x 965

mm



